



FIRES FOR DREAM HOMES





FIRES FOR DREAM HOMES

Apart from great products, we offer clients our in-depth knowledge, craftsman-like expertise and an inspiring range of finished projects to help you achieve your dream fireplace.

We are your one stop specialist centre for anything to do with the best and latest fireplace inserts and installation technology.

Maison Fireplaces heating systems are unparalleled in design, heating performance, efficiency, ease of operation and product versatility.

Our fireplaces provide warmth, ambience and a comforting focal point in many Australian homes.



ARLBERG 780 SERIES

ARLBERG

Competitively priced yet a powerful performer boasting premium looks and cutting edge technology, this fireplace's large glass area provides a calming ambience when viewing the fire.

ARLBERG TUNNEL

Desirable double sided design with standard side door opening system. Great performance and easy installation.

ARLBERG CASSETTE (Eco - green sign)

Perfect for installation in energy efficient houses and to retrofit in open fireplaces.

Easy operation, low wood consumption, optimised heating performance.

ARLBERG CORNER & THREE SIDED GLASS-DOOR (by special order)

Designer fireplace models for special effect installations.

RECOMMENDED INSTALLATION SYSTEMS

Natural convection, hot air transfer, heat storage system, hydronic central heating.

/ 480 mm / 1320 - 1450 / 535 mm
/ 1320 - 1450 / 535 mm
- 300 kg
ch
25 mm
0 mm / 550 mm
m / 35 cm
/ hour
W
W
* *
1

^{*} Due to the model variations within each series these dimensions and weights are indicative. Please refer to a technical sheet of an individual model for more accurate weights and measurements.

GLASS-DOOR CONFIGURATIONS



ARLBERG







ARLBERG TUNNEL



ARLBERG TRIPPLE-SIDED GLASS



ARLBERG CASSETTE





MT BLANC 970 SERIES

MT BLANC VD (vertical lift door)

The flagship of our range, this fireplace has a large door/glass area and popular vertical opening door. High heating performance, optimised dimensions, smart design and technology ideal for many applications.

MT BLANC SD (side opening door)

Same as Mt Blanc VD, only with swing door and attractive price tag.

MT BLANC TUNNEL

Highly sought after model, double sided version of the ever popular Mt Blanc.

MT BLANC AQUA-TECH

Special application model for hydronic central heating installation. Huge space and water heating capacity, this fireplace represents the pinnacle in heating technology.

RECOMMENDED INSTALLATION SYSTEMS

Natural convection, hot air transfer, heat storage system, hydronic central heating.

860 / 480 mm
970 / 1320 - 1550 / 535 mm
185 - 330 kg
8 inch
1 x 125 mm
1300 mm / 650 mm
55 cm / 40 cm
4.5 kg / hour
80%
15 kW
25 kW
Side, Lift

^{*} Due to the model variations within each series these dimensions and weights are indicative. Please refer to a technical sheet of an individual model for more accurate weights and measurements.

GLASS-DOOR CONFIGURATIONS



MT BLANC VD (vertical door)







MT BLANC SD (side opening door)



MT BLANC CORNER GLASS



MT BLANC TUNNEL 1xVD, 1xSD



MT BLANC TRIPPLE-SIDED GLASS





MT BLANC PANORAMA 1170 SERIES

MT BLANC PANORAMA 1170

Architecturally-styled fireplace with excellent heating characteristics. Vertical door for easy and elegant operation.

MT BLANC PANORAMA 1170 TUNNEL

Extra large glass areas for unlimited view of the fire. 1x vertical door (VD) 1x standard door (SD) for practical operation and seamless installation.

MT BLANC PANORAMA 1170 TUNNEL ALFRESCO

Especially designed tunnel unit for indoor/outdoor style installations. Cutting edge technology ensures most of the heat is directed inwards, outside surfaces are weather proofed and equipped with lock mechanism.

RECOMMENDED INSTALLATION SYSTEMS

Natural convection, hot air transfer, heat storage system.

Door dimensions (w h)	1060 / 480 mm
Overall dimensions (w h d)*	1170 / 1500 / 545 mm
Weight*	325 - 390 kg
Flue outlet	9 inch
Air supply duct	1 x 150 mm
Minimum hearth dimensions (w d)	1500 mm / 750 mm
Log length /diameter	60 cm / 45 cm
Average wood consumption	5 kg / hour
Average efficiency EU	80%
Nominal heat output	16 kW
Maximum heat output	30 kW
Door opening system	Lift

^{*} Due to the model variations within each series these dimensions and weights are indicative. Please refer to a technical sheet of an individual model for more accurate weights and measurements.

GLASS-DOOR CONFIGURATIONS

MT BLANC PANORAMA

MT BLANC PANORAMA TUNNEL



MT BLANC PANORAMA ALFRESCO For indoor/alfresco installation - outdoor paint





MT BLANC GRAND SERIES 1370 & 1570

MT BLANC GRAND 1370 & 1570

Totally unique fireplace inserts grand in design, size and construction.

Impressive heat output, yet clean efficient combustion and unparalleled ambience.
Suitable for large spaces or special effect applications.

RECOMMENDED INSTALLATION SYSTEMS

Natural convection, hot air transfer.

Door dimensions (w h)	1260, 1460 / 480 mm
Overall dimensions (w h d)*	1370 - 1570 / 1500 / 545 mm
Weight*	440 kg
Flue outlet (1370 / 1570)	9 inch / 10 inch
Air supply duct	2 x 125 mm
Minimum hearth dimensions (w d)	1800 mm / 850 mm
Log length /diameter	60 cm / 45 cm
Log length / diameter	00 CIII / 43 CIII
Average wood consumption	6 kg / hour
Average wood consumption	6 kg / hour
Average wood consumption Average efficiency EU	6 kg / hour 80%
Average wood consumption Average efficiency EU Nominal heat output	6 kg / hour 80% 18 kW

^{*} Due to the model variations within each series these dimensions and weights are indicative. Please refer to a technical sheet of an individual model for more accurate weights and measurements.

GLASS-DOOR CONFIGURATIONS





TATRA SERIES

This vertically styled fireplace is one of its kind, not to be found anywhere else in Australia.

Crystal clean combustion combined with tall burning flames create a totally unique effect and comforting experience.

It lends itself to a variety of designs and applications.

Can be installed as a free standing large volume, high capacity designer fireplace.

RECOMMENDED INSTALLATION SYSTEMS

Natural convection, hot air transfer, heat storage system, free standing designs.



Optional free standing design.

Door dimensions (w h)	510 / 750 mm
Overall dimensions (w h d)*	550 / 1370 / 505 mm
Weight*	210 kg
Flue outlet	8 inch
Air supply duct	1 x 125 mm
Minimum hearth dimensions (w d)	800 mm / 650 mm
Log length /diameter	40 cm / 35 cm
Average wood consumption	4 kg / hour
Average efficiency EU	79%
Nominal heat output	13 kW
Maximum heat output	25 kW
Door opening system	Side, Lift optional

^{*} Due to the model variations within each series these dimensions and weights are indicative. Please refer to a technical sheet of an individual model for more accurate weights and measurements.

GLASS-DOOR CONFIGURATIONS





5 YEAR/1 YEAR WARRANTY KEY FEATURES & TECHNOLOGY 5 YEARS (STEEL CASING) / 1 YEAR CONSUMABLES (SEALS, VERMICULITE, CAST IRON GRATE, ASH PAN)

Optional double glazing.



BEAUTIFULLY BUILT BY



Heat bank options.

Thermodynamic firebox with latest rib lining.

senotherm® UHT-HYDRO

Revolutionary non-smoking paint. No odours or harmful chemicals.

senotherm

| UHT-HYDRO |

KOBOK fireplace inserts are coated with ecological paint Senotherm® UHT-HYDRO Worldwide unique, entirely water-based, extremely hard surface, smoke/odour free

WEILBURGER, GERMAN TECHNOLOGY

on first use.



Clean combustion. Smoke-free chimney.





Rear loading door option.



Number of glazing options. Single, double, triple, quad.





Provision for connection of combustion air from the exterior.



Agua-tech system. Fireplaces equipped with hot water exchanger.



One handle air regulator and cast iron grate.



Optional gold or stainless steel finish.



Optimised for Australian wood and burning conditions.





INSTALLATION SYSTEMS



AKUMOL

SKAMOTEC 225 Enclosure - Natural Convection System

WHEN YOU WANT A QUALITY SYSTEM

Practical for installation into existing open fireplaces. Also great choice for energy efficient or passive buildings SKAMOTEC 225 is a high heat resistance calcium silicate board with several advantages.








No hazardous particles released during processing



CE and A1 certified. 100 % non-combustible material



Easy and fast processing and installation







BUILDING BOARDS FOR FIREPLACE ENCLOSURES

SKAMOTEC 225 is a lightweight non-combustible board with an excellent R-value, high mechanical strength and low thermal conductivity ideally suited for building fireplace

THE ADVANTAGE OF SKAMOTEC 225

It eliminates the use of traditional frame construction, making it easier and faster to install, for labour-saving efficiency.

PERFORMANCE BENEFITS

- Non-combustible (class A1)
- Excellent insulation value
- Ease of installation; lightweight and rigid
- Easy to shape with ordinary woodworking tools
- Ideal for renovation additions and new construction
- Environmentally friendly

THE PERFECT PARTNERS FOR SKAMOTEC 225

The perfect partners to our innovative SKAMOTEC 225 building boards are the SKAMOTEC EASYMIX and SKAMOLEX™ GLUE.

SKAMOTEC EASYMIX is a fast curing cement and fibre based lightweight universal mortar for jointing, filling and surface finishing that requires only the addition of water.

- · It has a particularly good workability
- It hardens faster than other similar products
- Easy to install on SKAMOTEC 225

SKAMOLEX™ GLUE is a water-borne adhesion to porous surfaces. It is inorganic and non-cementitious and is used for mounting of SKAMOTEC 225 fireplace building boards.





AKUMOL Enclosure - Heat Storage System

AKUMOL - OPTIMAL CHOICE FOR HEAT STORAGE FIREPLACE ENCLOSURE SYSTEMS

AKUMOL is a refractory building material especially developed for construction of heat retaining fireplace enclosures, ovens and cooking appliances.

It boasts special thermal properties which result in optimised transfer and retention of heat over a long period of time.

FEATURES

- Safe non toxic composition
- · High thermal conductivity
- Excellent heat storing properties
- Tough dust free surface
- Optimized for heat tolerant render finishes
- Extremely tough, long lasting fireplace enclosures

APPLICATIONS

Excellent thermal properties of Akumol make it a material of choice for construction of fireplace enclosures, ovens and other structures exposed to heat.

Large choice of profiles allow for freedom of design and ease of construction while maintaining high structural integrity. Heat tolerant, high bond mortar (Rudomal) is used for joining the bricks, (Brulla White) render for finishing the enclosure.

AKUMOL PROFILES


- Akumol Slab 500x250x40mm
- Akumol Slab Ledge 500x250x40mm
- Akumol Slab Corner 125x250x250x40mm
- Akumol Slab Corner Ledge 125x 250x250x40mm
- Akumol Ledge Filler Plate 220x110x25mm
- Akumol ¼ circle R350/250

THE PERFECT PARTNERS FOR AKUMOL REFRACTORY **BRICKS**

- Akumol refractory bricks
- Rudomal 1100 high bond mortar
- Hurdis board
- Brulla heat conductive render
















BUILDING MATERIALS





MAISON FIREPLACES Pty Ltd

10 Crosby's Lane Mansfield 3722 VIC

Tel +61 (0)409 353 331 info@maisonfireplaces.com.au

www.maisonfireplaces.com.au